

Ontario Power Generation Nuclear Report Card

*Darlington Nuclear
Second Quarter 2003*



A Report Card is also available for Pickering Nuclear.
Report Cards are issued on a quarterly basis.

ONTARIOPOWER
GENERATION

Why a Report Card?

We issue our Nuclear report card as part of keeping our promise to operate in an open manner — in this case by providing key statistics on how well our nuclear stations are working.

The measurements chosen for use in the report card represent only a few of those we use to assess our performance.

The report card also compares our performance with industry benchmarks which are based on industry best practices or performance of top performing nuclear utilities. To learn more about our performance, please visit the Ontario Power Generation website at www.opg.com or call 905-623-7122.

(continued on next page)




Public Safety

One gauge of how safe our stations are is the number of events that cause some reduction in the margin of public safety. Such events, in themselves, don't necessarily pose a danger to the public, but they do put pressure on the station's safety systems and therefore temporarily reduce the *margin* of safety.

This report card lists the number of Level 1 and 2 Reportable Events. A Level 1 Event is defined as highly significant. A Level 2 Event is significant.

Reportable Events ¹



¹ Data is cumulative

Reportable Events Summary:

There were two reportable events at Darlington in the second quarter of 2003, which brings the year-to-date total to three events. This meets the year-to-date target of three events. Both events were due to failure to fully close one of the approximately 450 steam doors in the plant.

Another significant measure of safety system performance is the "Reactor Trip Rate" — the number of unplanned reactor shutdowns (per 7,000 hours of operation) triggered by automatic safety systems. Reactor trips indicate potential problems that need to be addressed — but they also demonstrate that safety systems are working as they should to catch these potential problems.

Reactor Trip Rate Summary:

Through the second quarter, the year-to-date reactor trip rate measured zero, which is better than both our target and the industry benchmark of one trip per 7,000 hours of operation per year.



Radiation Exposure to the Public

Dose To Public ¹			
	Q2 2003 Actual (µSv)	Q2 2003 Target (µSv)	Performance
Darlington	0.5	3.8	Better than target

¹ Data is cumulative

This figure is an estimate of the radiation dose people would receive if they lived just outside the station boundary at their residences 24 hours a day, drank local water and milk, and ate local fish and produce. The dose is measured in microsieverts (µSv), an international unit of dose. By way of comparison, the average Canadian receives about 2,000 microsieverts a year from natural sources such as cosmic rays and radon in the soil.

Dose to Public Summary:

The Dose to Public was 87% better than target and significantly better than the regulatory limit of 1,000 microsieverts.

One important note. You'll see that on occasion we don't meet the targets we've set for ourselves. This doesn't indicate an unsafe situation. Our performance targets are set well within the range of safe operation. Any unsafe condition — or the potential of one — leads to the immediate shut-down of a reactor.


We're working hard to make our nuclear generating stations world performance leaders once again. We'll keep you informed of our progress through this report card.



Environmental Performance

The measure used to gauge environmental performance is the number of spills of chemicals or other substances that have taken place at the stations. These figures indicate "major and moderate preventable spills" reportable to the Ontario Ministry of the Environment.

Preventable Spills¹



¹ Data is cumulative

Preventable Spills Summary:


In the second quarter, there were no major or moderate spills. This meets target.



Employee Safety

One of the most widely accepted measures of employee safety is the Industrial Safety Accident Rate — the number of employee accidents per 200,000 hours worked that result in lost time, injuries that restrict work, or fatalities.

Industrial Safety Accident Rate



Industrial Safety Accident Rate Summary:

There were no accidents in the second quarter at Darlington. However, two minor accidents that resulted in employee absences from work during the first quarter continue to impact this indicator's performance. Nevertheless, the year-to-date figure of 0.18 is better than the target of 0.24 employee accidents per 200,000 hours worked.

Another useful measure of employee safety is the Accident Severity Rate — the number of days lost to injuries per 200,000 hours worked.

Accident Severity Rate Summary:

The year-to-date Accident Severity Rate measured 0.57 in the second quarter. This result is better than the target of 0.74 days lost to injuries per 200,000 hours worked.







Electricity Production

One measure of how well the station is doing at producing electricity is the “Capability Factor.” This figure represents the amount of electricity the station is actually capable of producing per quarter as a percentage of its potential capacity — in other words, its capacity if all reactors and related systems were operating with no down-time at all.

Capability Factor Summary:

The Capability Factor of 89.9% was better than the target of 87.8% to the end of June.

Capability Factor




Nuclear Performance Index

This index, reported on a quarterly basis, is measured out of 100 and provides an overview of performance based on 10 key indicators that cover a number of areas, including safety and production. The index is used by the World Association of Nuclear Operators (WANO) as one measure of a nuclear plant’s performance.

Nuclear Performance Index Summary:

The Q2 2003 Nuclear Performance Index (NPI) is 93.4, which is better than the target of 91.8. This quarter’s NPI represents an increase of 0.9 points from Q1 2003.

Nuclear Performance Index



Glossary

Index: A collection of statistics that, taken together, provide a useful standard or measurement.

WANO: World Association of Nuclear Operators — an international organization created to maximize the safety and reliability of the operation of nuclear power plants worldwide.

YE: Year-end

YTD: Year-to-date

Ontario Power Generation is an Ontario-based company, whose principal business is the generation and sale of electricity to customers in Ontario and to neighbouring markets. OPG’s goal is to be a premier North American company focused on low-cost power generation and wholesale energy sales while operating in a safe, open and environmentally responsible manner. For more information, please call 905-623-7122 or visit our website at www.opg.com